

G2XH 2-Wire Braid Xtreme® Heat Hose - SAE 100R2 Type S High Pressure

Continued

HOSE	Description	Product No.						Standard Pack	Weight (Lbs.)
HOSE/CPLG. SELECTION	4G2XHXREEL	4657-2541	1/4	.59	6000	24000	4.0	550	.30
G8K COUPLINGS	6G2XH X50FT	4657-4009	3/8	.74	5000	20000	5.0	1	17.50
	6G2XHXREEL	4657-2542	3/8	.74	5000	20000	5.0	400	.39
GLOBALSPIRAL COUPLINGS	8G2XH X50FT	4657-4010	1/2	.86	4250	17000	7.0	1	22.60
	8G2XHXREEL	4657-2543	1/2	.86	4250	17000	7.0	330	.47
PCM / PCS FERRULES	10G2XH X50FT	4657-4011	5/8	.99	3625	14500	8.0	1	27.20
	10G2XHXREEL	4657-2544	5/8	.99	3625	14500	8.0	220	.56
MEGACRIMP COUPLINGS	12G2XH X50FT	4657-4012	3/4	1.15	3100	12400	9.5	1	32.00
	12G2XHXREEL	4657-2545	3/4	1.15	3100	12400	9.5	220	.68
STAINLESS STEEL	16G2XH X50FT	4657-4013	1	1.48	2500	10000	12.0	1	49.60
	16G2XHXREEL	4657-2546	1	1.48	2500	10000	12.0	165	1.02
POWER CRIMP COUPLINGS	20G2HXCTN	4657-4988	1 1/4	1.86	2250	9000	16.5	130	1.82
	24G2HXCTN	4657-4989	1 1/2	2.15	1800	7200	20.0	130	1.50
	32G2HXCTN	4657-4990	2	2.65	1500	6000	25.0	130	2.12

Global G2H High-Temp 2-Wire Braid Hose Type AT High Pressure

Meets Flame Resistance Acceptance Designation "MSHA 2G"

Recommended For: High temperature high-pressure hydraulic oil lines. Meets or exceeds the requirements of SAE 100R2, ISO1436 2SN R2 and EN 853 2SN.

Tube: Black, oil resistant, synthetic rubber (Nitrile - Type C). See Hose Stock Characteristics.

Reinforcement: Two braids of high-tensile steel wire.

Cover: Black, oil resistant, synthetic rubber (CSM - Type M). Also available with unique abrasion resistant MegaTuff® cover. See Hose Stock Characteristics.

Temperature Range: -40°F to +275°F (-40°C to +135°C) constant and +300°F (+149°C) intermittent (up to 10% of operating time). For water emulsions see Temperature Limits Table.

Coupling Recommendation (See gates.com/ecrimp or Crimp Data Manual 35019)

Field Attachable Type T Couplings (-20 and -24) (Section O)

GlobalSpiral™ Couplings (-20) (Section E)

GlobalSpiral™ Plus Couplings (-24 and -32) (Section E)

MegaCrimp® Couplings (-20) (Section G)



HOSE	Description	Product No.						Standard Pack	Weight (Lbs.)
SURELOK AIR BRAKE COUPLINGS	20G2H X50FT	4657-0925	1 1/4	1.86	1825	6500	16.5	1	75.75
	20G2HXCTN	4657-0930	1 1/4	1.86	1825	6500	16.5	120	1.52
ADAPTERS	24G2H X25FT	4657-4331	1 1/2	2.11	1300	5200	20.0	1	45.00
	24G2H X50FT	4657-0927	1 1/2	2.11	1300	5200	20.0	1	90.06
QUICK DISCONNECT COUPLERS	24G2HXCTN	4657-0931	1 1/2	2.11	1300	5200	20.0	120	1.80
	32G2H X25FT	4657-4332	2	2.62	1175	4700	25.0	1	57.25
LIVE SWIVEL	32G2H X50FT	4657-0926	2	2.62	1175	4700	25.0	1	114.29
	32G2HXCTN	4657-0932	2	2.62	1175	4700	25.0	120	2.29
BALL VALVES									
ACCESSORIES									
EQUIPMENT AND PARTS									