



Air and Multi-Purpose Hose

Adapta Flex™ Blue, Green & Yellow Cover
(Specification 3204BL, GR, YL)

	Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
Color	(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
Blue	1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1496	\$1.61
Blue	3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	X	3204-1497	1.98
Blue	3/8	9.5	.69	17.5	300	2.07	30.0	762	3.0	76	.15	.07	Reel	25,000 ft.	3204-1501	2.30
Blue	1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	X	3204-1498	2.37
Blue	1/2	12.7	.83	21.1	300	2.07	25.0	635	5.0	127	.20	.09	Reel	25,000 ft.	3204-1503	2.82
Blue	3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	X	3204-1500	3.36
Blue	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	Reel	X	3204-1505	3.68
Blue	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	50 ft.	200 ft. (X)	3204-0560	3.68
Green	1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1516	1.61
Green	3/8	9.5	.69	17.5	300	2.07	30.0	762	3.0	76	.15	.07	Reel	25,000 ft.	3204-1511	2.30
Green	3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	25,000 ft.	3204-1517	1.98
Green	1/2	12.7	.83	21.1	300	2.07	25.0	635	5.0	127	.20	.09	Reel	25,000 ft.	3204-1513	2.82
Green	1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	25,000 ft.	3204-1518	2.37
Green	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	Reel	X	3204-1515	3.68
Green	3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	25,000 ft.	3204-1520	3.36
Green	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	50 ft.	200 ft. (X)	3204-0506	3.68
Yellow	1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1526	1.61
Yellow	3/8	9.5	.69	17.5	300	2.07	30.0	762	3.0	76	.15	.07	Reel	25,000 ft.	3204-1521	2.30
Yellow	3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	25,000 ft.	3204-1527	1.98
Yellow	1/2	12.7	.83	21.1	300	2.07	25.0	635	5.0	127	.20	.09	Reel	25,000 ft.	3204-1523	2.82
Yellow	1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	X	3204-1528	2.37
Yellow	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	Reel	25,000 ft.	3204-1525	3.68
Yellow	3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	25,000 ft.	3204-1530	3.36
Yellow	3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.37	.17	50 ft.	200 ft. (X)	3204-0558	3.68

- RECOMMENDED FOR:

Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in-plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides.
- TEMPERATURE:

-40°F to +200°F (-40°C to +93°C) continuous service.
- CONSTRUCTION:

Tube:

Type P (EPDM). Black.

Reinforcement:

Synthetic, high tensile textile cord.

Cover:

Type P (EPDM). Blue, Green or Yellow. All sizes through 1/2" are perforated.

Design Factor:

3:1
- COUPLINGS:

19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 72 Gates Power Crimp® or 75 Gates GLX®. Reference the Hose Coupling Section.
- PACKAGING:

Minimum of 90% of hose reels will be 1-piece lengths.
3/8" through 3/4": Packaged in 500' to 700' reels. Maximum 2 pieces in 50' increments.
3/4" x 50': Packaged 200' per carton, each length coiled and tied.
- BRANDING:

Continuous ink brand. Example: "GATES® ADAPTA FLEX™ MULTI-PURPOSE 3/8 INCH (9.5mm) 300 PSI (2.07MPa) WP MADE IN USA"
- SPECIAL ORDER REQUIREMENTS:

Special production runs require minimum order quantities of 25,000 feet per size.
- REMNANT LENGTHS:

None.
- STANDARDS:

Tube:

ARPM (Class C) Limited oil resistance.

ACID-CHEMICAL
AIR AND MULTI-PURPOSE
FOOD AND BEVERAGE
MARINE
MATERIAL HANDLING
MINING
OILFIELD
PETROLEUM TRANSFER
PRESSURE WASHER
STEAM
WATER
CLAMPS
COUPLINGS AND FERRULES
HOSE FINDER
CHEMICAL RESISTANCE TABLE

