



Material Handling Hose

429W (Sand Blast)
(Specification 4129A)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1/2	12.7	1.23	31.2	150	1.03	25.0	635	5.0	127	.55	.25	50 ft.	X	4129-0085	\$11.46
3/4	19.1	1.50	38.1	150	1.03	15.0	381	8.0	203	.70	.32	50 ft.	X	4129-0086	15.00
1	25.4	1.87	47.5	150	1.03	5.0	127	12.0	305	.96	.44	50 ft.	X	4129-0100	21.09
1	25.4	1.63	41.4	150	1.03	5.0	127	12.0	305	.70	.32	50 ft.	X	4129-0256	18.53
1 1/4	31.8	2.16	54.9	150	1.03	5.0	127	12.0	305	1.12	.51	50 ft.	X	4129-0105	25.32
1 1/2	38.1	2.37	60.2	135	.93	5.0	127	18.0	457	1.56	.71	50 ft.	X	4129-0150	28.20
2	50.8	2.94	74.7	120	.83	5.0	127	20.0	508	2.00	.91	50 ft.	X	4129-0200	35.72

- RECOMMENDED FOR:

Sand, shot blasting work and wherever abrasive materials are carried at high velocity.
- TEMPERATURE:

-40°F to +150°F (-40°C to +66°C) continuous service.
- CONSTRUCTION:

Tube:

Type D3 (Natural Rubber). Black. Static conductive.

Reinforcement:

Synthetic, high tensile textile.

Cover:

Type D (SBR). Black with yellow spiral stripe. All sizes are perforated.

Design Factor:

4:1
- COUPLINGS:

36. Reference the Hose Coupling Section.
- PACKAGING:

50' length coiled and wrapped in polyethylene.
- BRANDING:

Continuous transfer label. Example: "GATES® 429W Sandblast 150 PSI (1.03MPa) WP Made In Mexico"
- SPECIAL ORDER REQUIREMENTS:

All sizes are wrapped construction, 50 foot maximum length. Special production runs require minimum order quantities of 600 feet per size. If a special transfer label is required, contact Gates Corporation for minimum quantity.
- REMNANT LENGTHS:

None.

ACID- CHEMICAL
AIR AND MULTI- PURPOSE
FOOD AND BEVERAGE
MARINE
MATERIAL HANDLING
MINING
OILFIELD
PETROLEUM TRANSFER
PRESSURE WASHER
STEAM
WATER
CLAMPS
COUPLINGS AND FERRULES
HOSE FINDER
CHEMICAL RESISTANCE TABLE

