



Marine Hose

Wet Exhaust (Softwall)
(Specification 3137ME)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ea.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ea.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1 1/8	28.6	1.40	35.6	100	.69	—	—	—	—	5.59	2.54	12 1/2 ft.	X	3137-1207	\$217.50
1 1/4	31.8	1.53	38.9	100	.69	—	—	—	—	6.07	2.76	12 1/2 ft.	X	3137-1209	228.38
1 3/8	34.9	1.69	42.9	100	.69	—	—	—	—	6.58	2.99	12 1/2 ft.	X	3137-1213	243.38
1 1/2	38.1	1.78	45.2	100	.69	—	—	—	—	7.12	3.24	12 1/2 ft.	X	3137-1215	251.07
1 5/8	41.3	1.91	48.5	100	.69	—	—	—	—	7.63	3.47	12 1/2 ft.	X	3137-1217	259.32
1 3/4	44.5	2.03	51.6	100	.69	—	—	—	—	8.15	3.70	12 1/2 ft.	X	3137-1219	264.20
1 7/8	47.6	2.19	55.6	100	.69	—	—	—	—	8.63	3.92	12 1/2 ft.	X	3137-1221	270.75
2	50.8	2.32	58.9	100	.69	—	—	—	—	9.18	4.17	12 1/2 ft.	X	3137-1223	285.95
2 1/8	54.0	2.45	62.2	100	.69	—	—	—	—	9.69	4.40	12 1/2 ft.	X	3137-1225	305.63
2 1/4	57.2	2.57	65.3	100	.69	—	—	—	—	10.00	4.55	12 1/2 ft.	X	3137-1227	311.25
2 3/8	60.3	2.69	68.3	100	.69	—	—	—	—	10.70	4.86	12 1/2 ft.	X	3137-1229	315.00
2 1/2	63.5	2.82	71.6	100	.69	—	—	—	—	11.24	5.11	12 1/2 ft.	X	3137-1231	329.25
2 5/8	66.7	2.95	74.9	100	.69	—	—	—	—	11.79	5.36	12 1/2 ft.	X	3137-1233	365.45
2 3/4	69.9	3.09	78.5	100	.69	—	—	—	—	12.29	5.59	12 1/2 ft.	X	3137-1235	389.07
2 7/8	73.0	3.23	82.0	100	.69	—	—	—	—	12.80	5.82	12 1/2 ft.	X	3137-1237	395.63
3	76.2	3.36	85.3	100	.69	—	—	—	—	14.45	6.57	12 1/2 ft.	X	3137-1239	409.32
3 1/2	88.9	3.86	98.0	100	.69	—	—	—	—	16.63	7.56	12 1/2 ft.	X	3137-1245	457.50
4	101.6	4.36	110.7	100	.69	—	—	—	—	18.57	8.44	12 1/2 ft.	X	3137-1249	529.70
4 1/2	114.3	4.86	123.4	100	.69	—	—	—	—	21.00	9.55	12 1/2 ft.	X	3137-1252	590.63
5	127.0	5.37	136.4	100	.69	—	—	—	—	23.35	10.61	12 1/2 ft.	X	3137-1253	699.95
6	152.4	6.38	162.1	100	.69	—	—	—	—	27.14	12.34	12 1/2 ft.	X	3137-1254	909.95

- RECOMMENDED FOR:

Heavy-duty fabric reinforced. Designed for use where wire support is not required. Meets marine water and wet exhaust hose requirements. May be used for engine water circulation, discharge lines, heat exchangers and straight wet exhaust connections.
- TEMPERATURE:

-40°F to +257°F (-40°C to +125°C) continuous service.
- CONSTRUCTION:

Tube:

Type P (EPDM). Black.

Reinforcement:

Two plies of synthetic fabric.

Cover:

Type P (EPDM). Black with blue spiral stripe.

Design Factor:

4:1
- PACKAGING:

All lengths packaged in polyethylene wrap.
- BRANDING:

Continuous transfer label. Example: “GATES® MARINE WET EXHAUST SOFTWALL 100 PSI WP MADE IN U.S.A.”
- SPECIAL ORDER REQUIREMENTS:

Special production runs require minimum order quantities of 200 feet.
- REMNANT LENGTHS:

None.
- STANDARDS:

Meets requirements of SAE J2006 R1.

