

## **GATES INDUSTRIAL HOSE PRODUCTS**

ACID-CHEMICAL

AIR AND MIIITI-**PURPOSE** 

FOOD AND BEVERAGE

MARINE

MATERIAL **HANDLING** 

MINING

**OILFIELD** 

**PETROLEUM** TRANSFER

PRESSURE WASHER

STEAM

WATER

**CLAMPS** 

COUPLINGS AND **FERRULES** 

HOSE **FINDER** 

**CHEMICAL** RESISTANCE TABLE



## **Pressure Washer**

Cyclone® (Specification 3217HY)

Nom. I.D.	$\Theta$	Nom. O.D.	Ō	Max. W.P.	<b>©</b>	Suction	0	Min. Bend Radius	P	Wt. Per Ft.	Å	Standard	Stock (X) or Minimum	Gates	List Price
(In.)	(mm)	(ln.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack	Order Qty.	Item No.	Per Ft.
3/8	9.5	.73	18.5	1000	6.90	30.0	762	4.0	102	.18	.08	Reel	X	3217-0585	\$5.63
3/8	9.5	.73	18.5	1000	6.90	30.0	762	4.0	102	.18	.08	100 ft.	X	3217-0584	6.35
1/2	12.7	.94	23.9	1000	6.90	30.0	762	5.0	127	.29	.13	Reel	X	3217-0586	7.80
1/2	12.7	.94	23.9	1000	6.90	30.0	762	5.0	127	.29	.13	100 ft.	5,000 ft.	3217-0587	8.82
3/4	19.1	1.20	30.5	1000	6.90	30.0	762	6.0	152	.41	.19	Reel	X	3217-0588	12.38

High-pressure washer operations using mild detergents in meat and poultry plants. Cover is resistant to weather, oil, animal fat, abrasion and heat encountered in packing plant cleaning applications. **RECOMMENDED FOR:** 

**CAUTION:** Air service working pressure is 300 psi for all sizes.

**TEMPERATURE:** -40°F to +212°F (-40°C to +100°C) continuous washdown service.

**CONSTRUCTION:** Type C2 (Modified Nitrile). Black. **Reinforcement:** 

Braided, synthetic high tensile cord.

Type C2 (Modified Nitrile). Yellow. (Red, gray and blue cover available on special order). All colors non-marking. Cover:

**Design Factor:** 4:1

**COUPLINGS:** 75 Gates GLX®. Reference the Hose Coupling Section.

3/8" through 3/4": Packaged in 500' to 750' reels. Maximum 3 pieces. Minimum length 50'. PACKAGING:

3/8" x 100': Packaged in 100' exact lengths, packaged 500' in a pallet box. Each length coiled and tied. 1/2" x 100': Packaged in 100' exact lengths, packaged 500' in a pallet box. Each length coiled and tied.

Continuous ink print label. Example: "GATES" Cyclone" Washdown 3/8 Inch (9.5mm) 1000 PSI (6.90MPa) WP Made In U.S.A." **BRANDING:** 

SPECIAL ORDER REQUIREMENTS: Red, gray and blue covers are made to order and require 5,000 feet orders per size/color. Contact Gates Corporation for pricing, order requirements and availability.

Special production runs require minimum order quantities of 5,000 feet per size. For special requirements contact Gates Corporation.

**REMNANT LENGTHS:** 

