Food and Beverage Hose

AGRICULTURE

AIR BREATHING

AIR DUCT

AIR AND MULTI-PURPOSE

CHEMICAL

FOOD AND BEVERAGE

MARINE AND ENGINE

MATERIAL HANDLING

MINING

OILFIELD

PETROLEUM

PRESSURE WASH AND WASHDOWN

STEAM

WATER

CLAMPS

COUPLINGS AND FERRULES

HOSE FINDER

CHEMICAL RESISTANCE TABLE

Food Master® Oils and Dairy 150D

Formerly - Sani-Pure™



Color	Hose I.D.	Θ	Hose O.D.	<u>[O</u>	Max. W.P.	(7 2-2)	Vac.	MBR	Wt. Per ft	Length	Std.	Pkg Code	Stock or MTO	Gates Item No.	List Price Per ft
	(in)	(mm)	(in)	(mm)	(psi)		(In. Hg)		(Lbs.)	(ft)		Oode	(ft)		
White	1 1/2	38.1	2.04	51.8	150	10.3	_	18.0	.97	100	PLT	Т	MTO	3131-0001	\$26.85
White	2	50.8	2.54	64.5	150	10.3	-	24.0	1.25	100	PLT	Т	Stock	3131-0002	33.08
White	2 1/2	63.5	3.06	77.7	150	10.3	_	30.0	1.66	100	PLT	T	MTO	3131-0003	42.24
White	3	76.2	3.56	90.4	150	10.3	-	36.0	1.90	100	PLT	T	MTO	3131-0004	47.69
White	4	101.6	4.60	116.8	150	10.3	-	48.0	2.78	100	PLT	Т	MTO	3131-0005	67.88
White	6	152.4	6.60	167.6	150	10.3	_	72.0	4.10	50	PLT	Т	MTO	3131-0006	108.41

RECOMMENDED FOR: Tank truck, barge, ship, or storage tank transfer (discharge only) of a variety of food products such as animal fat, vegetable oil and other edible oils at temperatures up to +230°F requiring FDA sanitary hose. Also suitable for ice cream and other dairy products requiring 3A—Class 3 standards.

TEMPERATURE: -40°F to +230°F (-40°C to +110°C) continuous service.

CONSTRUCTION: Type C2 (Modified Nitrile). Sanitary FDA and 3A-Class 3. White.

Reinforcement:

Synthetic, high tensile textile.

Type C2 (Modified Nitrile). White with burgundy stripe.
4:1 Cover:

Design Factor:

COUPLINGS: 1 or stainless steel, 8 or stainless steel, 34, 71. Reference the Hose Coupling Section.

STANDARDS: Tube meets FDA requirements, 3A–Class 3 and USDA. Phthalate free.