Petroleum Hose

Fuel Master[™] 150SD LT MegaFlex[®]

Formerly - Arctic Longhorn® MegaFlex®



Color	Hose I.D.	Θ	Hose O.D.	Ō	Max. W.P.	©	Vac.	MBR	Wt. Per ft	Length	Std.	Pkg Code	Stock or MTO	Gates Item No.	List Price Per ft
Color	(in)	(mm)	(in)	(mm)	(psi)	(Bar)	(In. Hg)	(in)	(Lbs.)	(ft)	Pack	Code	(ft)	item No.	Peril
Blue	2	50.8	2.38	60.5	150	10.3	30.0	2.0	1.13	100	PLT	Т	Stock	4688-2040	\$27.82
Blue	2	50.8	2.38	60.5	150	10.3	30.0	2.0	1.13	200	PLT	Т	MTO	4688-2041	27.82
Blue	3	76.2	3.44	87.4	150	10.3	30.0	3.0	1.61	100	PLT	Т	Stock	4688-2042	38.52
Blue	3	76.2	3.44	87.4	150	10.3	30.0	3.0	1.13	200	PLT	Т	МТО	4688-2043	38.52
Blue	4	101.6	4.49	114.0	150	10.3	30.0	4.0	1.13	100	PLT	Т	Stock	4688-2044	51.59
Blue	4	101.6	4.49	114.0	150	10.3	30.0	4.0	1.13	200	PLT	Т	МТО	4688-2045	51.59

RECOMMENDED FOR: Transfer of refined fuels (commercial gasoline and diesel fuel), oils and other petroleum products. It is ideal for tank truck, fuel farm and oilfield service truck use where a super flexible cold weather fuel transfer hose is needed. Hose life can be extended by draining hose after use. Hose maintains flexibility down to -65°F.

CAUTION: Service life of transfer hoses can be extended by draining hoses after use.

TEMPERATURE: -65°F to +180°F (-54°C to +82°C) continuous service.

CONSTRUCTION:

Tube: Type C (Nitrile). Black.
Reinforcement: Cover: Type A (Chloroprene). Blue corrugated with black stripe.
Design Factor: 4:1

COUPLINGS: 7, 26, 49 or 78. (for ambient temperatures only). Reference the Hose Coupling Section.

STANDARDS: Tube: ARPM (Class A) High oil-resistance.

AGRICULTURE AIR BREATHING AIR DUCT AIR AND MULTI-PURPOSE CHEMICAL FOOD AND BEVERAGE MARINE AND ENGINE MATERIAL HANDLING MINING OILFIELD PETROLEUM

PRESSURE WASH AND WASHDOWN

STEAM

WATER

CLAMPS

COUPLINGS AND FERRULES

HOSE FINDER

CHEMICAL RESISTANCE TABLE

139 www.gates.com