Water Hose

AGRICULTURE

AIR BREATHING

AIR DUCT

AIR AND MULTI-PURPOSE

CHEMICAL

FOOD AND BEVERAGE

MARINE AND ENGINE

MATERIAL HANDLING

MINING

OILFIELD

PETROLEUM

PRESSURE WASH AND WASHDOWN

STEAM

WATER

CLAMPS

COUPLINGS AND FERRULES

HOSE FINDER

CHEMICAL RESISTANCE TABLE

Water Master® Water Suction/Discharge 150SD



	Hose I.D.	Θ	Hose O.D.	Ō	Max. W.P.	©	Vac.	MBR	Wt. Per ft	Length	Std.	Pkg	Stock or MTO	Gates	List Price
Color	(in)	(mm)	(in)	(mm)	(psi)	(Bar)	(In. Hg)	(in)	(Lbs.)	(ft)	Pack	Code	(ft)	Item No.	Per ft
Black	2	50.8	2.36	59.9	150	10.3	30.0	8.0	1.08	100	PLT	Т	Stock	4686-0751	\$10.08
Black	3	76.2	3.54	89.9	150	10.3	30.0	14.0	2.10	100	PLT	Т	Stock	4686-0752	13.92
Black	4	101.6	4.54	115.3	150	10.3	30.0	18.0	2.37	100	PLT	Т	MTO	4686-0753	19.80

NOTE: Made in Mexico.

Economical, medium to light–duty water suction/discharge for agricultural, construction and industrial applications. EPDM tube designed to handle a variety of liquids including Lasso^{®*}, Lasso II^{®*} and Freedom^{®*}. Recommended for sanitation liner in marine applications. (*Registered Trademarks of Monsanto) RECOMMENDED FOR:

TEMPERATURE: -40°F to +180°F (-40°C to +82°C). CONSTRUCTION:

Type P (EPDM). Black.
Synthetic, high tensile textile cord with steel wire helix.
Type P (EPDM). Black with blue stripe.
3:1 Reinforcement: Cover:

Design Factor:

COUPLINGS: 5, 6, 7, 8, 49 or 78 all sizes. Reference the Hose Coupling Section.