

GH663

MATCHMATE Plus

HI-IMPULSE

一层钢丝编织软管



符合或超过:

SAE 100R1AT S型、EN853 1SN、ISO 1436-1 1SN型

# 零件号	 软管内径		 软管外径		 最大工作压力		 最小爆破压力		 最小弯曲半径		 软管重量	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs/ft
GH663-4	6,4	0.25	13,5	0.53	227,0 192,0	3250† 2750	897,0 770,0	13000† 11000	100,0	4.00	0,24	0.16
GH663-6	9,7	0.38	17,5	0.69	210,0 157,0	3000† 2250	840,0 630,0	12000† 9000	125,0	5.00	0,37	0.25
GH663-8	12,7	0.50	20,6	0.81	175,0 140,0	2500† 2000	700,0 560,0	10000† 8000	180,0	7.00	0,45	0.30
GH663-12	19,1	0.75	27,7	1.09	124,0 87,0	1800† 1250	497,0 350,0	7200† 5000	241,3	9.50	0,67	0.45
GH663-16	25,4	1.00	35,8	1.41	90,0 70,0	1300† 1000	359,0 280,0	5200† 4000	304,8	12.00	1,01	0.68
GH663-20	31,8	1.25	43,4	1.71	66,0	950	260,0	3770	419,1	16.50	1,31	0.88
GH663-24	38,1	1.50	50,6	1.99	50,0	725	200,0	2900	508,0	20.00	1,56	1.05
GH663-32	50,8	2.00	64,0	2.52	40,0	580	160,0	2320	635,0	25.00	1,95	1.31

结构

合成橡胶内层，一层钢丝编织增强层，合成橡胶外层。

工作温度范围

-40°C到+100°C[-40°F到+212°F]

应用

石油基或水基液压油的液压系统，适用各种工业行业。有关特殊流体的应用和高温指标的更多资料，请参见第21页。

† 使用Eaton接头时性能将提高。