

FC687

二层钢丝编织软管



符合或超过:

SAE 100R2AT、EN853 2SN、ISO 1436-1 Type 2SN

# 零件号	 软管内径	 软管外径	 最大工作压力	 最小爆破压力	 最小弯曲半径	 软管重量
	mm in	mm in	bar psi	bar psi	mm in	Kg/m lbs/ft
FC687-04	6,4 0.25	15,0 0.59	400,0 5800	1600,0 23200	100,0 4.00	0,383 0.26
FC687-05	7,9 0.31	16,5 0.65	350,0 5075	1400,0 20300	115,0 4.53	0,435 0.29
FC687-06	9,5 0.38	18,9 0.74	330,0 4785	1320,0 19140	130,0 5.12	0,552 0.37
FC687-08	12,7 0.50	22,2 0.87	275,0 3988	1100,0 15950	180,0 7.09	0,650 0.43
FC687-10	16,0 0.63	25,2 0.99	250,0 3625	1000,0 14500	200,0 7.87	0,762 0.51
FC687-12	19,0 0.75	29,2 1.15	215,0 3118	860,0 12470	240,0 9.45	0,942 0.63
FC687-16	25,4 1.00	37,2 1.46	165,0 2393	660,0 9570	300,0 11.81	1,313 0.88
FC687-20	31,8 1.25	47,3 1.86	125,0 1813	500,0 7250	420,0 16.54	1,920 1.28
FC687-24	38,1 1.50	53,7 2.11	90,0 1305	360,0 5220	500,0 19.69	2,144 1.43
FC687-32	50,8 2.00	66,7 2.63	78,0 1131	312,0 4524	630,0 24.80	2,799 1.87

结构

合成橡胶内层，两层钢丝编织增强层，合成橡胶外层。

工作温度范围

-40°C到+100°C[-40°F到+212°F]

应用

石油基或水基液压油的液压系统，适用各种工业行业。有关特殊流体的应用和高温指标的更多资料，请参见第21页。