## PERFORMER AD10T

**CONSTRUCTION AND ENVIRONMENT** 

Abrasive materials hydraulic and pneumatic handling

Pneumatic or hydraulic suction or discharge of abrasive materials with high temperature. **Advantages** 

- Excellent resistance to abrasion at high temperature.
- Low installation cost.

**Applications** 

- Static conductivity ensured by the helix and by the antistatic tube.
- Suppression of pressure surges.
- Reduction in head loss.
- Damping of vibrations and noise.
- Many types of fittings possible.
- Excellent weather resistance.



## **Technical description**

Inner tube: EPDM, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather resistant EPDM, black, corrugated, fabric impression. Temperature range: - 30  $^{\circ}$ C to + 100  $^{\circ}$ C (peaks at + 110  $^{\circ}$ C). Electrical properties: conductive tube and cover.

Couplings/Fittings
Hoses can be fitted with:

- 2 END-FLEX®,
- 1 cuff + 1 END-FLEX® flange,
- 2 enlarged or smooth cuffs.

Hoses fitted with END-FLEX® flanges are allowed to work with pressure and vacuum mentioned in the table.

## **Complementary information**

Low stretch under 10 bar working pressure.

Hoses can be manufactured with straight or enlarged ends.

ID mm	OD mm		Tube thickness mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Max. length m	Notes
25.0	53.0	± 2	5.6	10	30	0.9	125	2.21	20	
32.0	60.0	± 2	5.6	10	30	0.9	160	2.65	20	
40.0	73.0	± 2	8.5	10	30	0.9	200	3.19	20	
50.0	83.0	± 2	8.5	10	30	0.9	250	4.24	20	
65.0	98.0	± 2	8.5	10	30	0.9	325	5.15	20	
75.0	108.0	± 2	8.5	10	30	0.9	375	5.78	20	
80.0	113.0	± 2	8.5	10	30	0.9	400	6.06	20	
100.0	133.0	± 2	8.5	10	30	0.9	500	7.32	20	
125.0	158.0	± 2	8.5	10	30	0.9	750	8.66	20	
150.0	183.0	± 2	8.5	10	30	0.9	1050	10.18	20	
175.0	208.0	± 2	8.5	10	30	0.9	1300	11.70	10	
200.0	234.5	± 2	8.5	10	30	0.9	1600	14.30	12	
250.0	285.5	± 2	8.5	10	30	0.9	2000	17.50	12	
300.0	340.5	± 2	8.5	10	30	0.9	2500	24.82	12	
350.0	391.0	± 3	8.5	10	30	0.9	3000	29.44	12	
400.0	441.0	± 3	8.5	10	30	0.9	3400	34.51	12	

Length in green = stock item. Length in black = non stock (consult us for minimum quantity of order). Branding:





and embossed: week/year