



# TRIX® Acetylene hose - red

For the safe transport of fuel gases - DIN EN ISO 3821

## Application

The TRIX® Acetylene hose red is designed for the transport of acetylene gases. It meets the latest regulations of the DIN EN ISO 3821 standard and thus offers the highest possible safety. The hose is extremely robust, flexible, resistant to ozone and weather and has a smooth, dirt-proof cover. The excellent quality is the reason, why the hose is most popular and is being used for decades in installation and heating system companies, foundries, shipyards, for the construction of bridges, in the steel and car body construction, over- and underground workings, in welding shops and at manufacturers of welding apparatus.

## Marking

"Continental ContiTech TRIX® AUTOGEN DN 9 DIN EN ISO 3821 2MPa (20 BAR / 290 PSI) Made in Germany" on red cover

## Description

- › Black, non-porous and smooth EPDM lining
- › Reinforcements: synthetic fibres
- › Red, smooth EPDM-cover, resistant to ozone, weather, UV and abrasion
- › Working pressure up to 20 bar / 290 psi
- › Temperature range from -40°C up to +60°C / -40°F up to +140°F
- › Highly flexible, robust
- › Non-buckling, dimensionally stable
- › Release agent- and fat-free, free from any product harmful to lacquer
- › Lining electrically conductive,  $R < 10^6 \Omega/m$
- › According to DIN EN ISO 3821

## Technical data

nominal width	inner-Ø	wall thickness	length	working pressure		min. burst pressure		min. bending radius	weight
Zoll/inch	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/m
1/6	4	3.5	40	20	290	60	870	15	130
1/4	6.3	3.5	40	20	290	60	870	25	170
3/8	9	3.5	40	20	290	60	870	35	210
7/16	11	3.5	40	20	290	60	870	55	250
1/2	12.5	4.5	40	20	290	60	870	50	370
5/8	16	4.5	40	20	290	60	870	65	430

Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability

