



CONTI® ULTIMATE Flange and Gasket

Mining Hose System

Flange

nominal width zoll/inch	inner- Ø mm	Betriebsdruck bar	psi	Bolt Circle Standard	aprx. g/m	ANSI	weight aprx. g/m
2	51	10	145	1400	150 lbs	1400	1400
3	76	10	145	2300	150 lbs	2300	2300
4	102	10	145	3900	150 lbs	3900	3900
5	127	10	145	6900	150 lbs	6900	6900
6	152	10	145	7800	150 lbs	7800	7800
8	204	10	145	12700	150 lbs	12700	12700
10	254	5	73	13100	150 lbs	13100	13100
12	305	5	73	21800	150 lbs	21800	21800
14	355	5	73	26400	150 lbs	26400	26400
14	355	5	73	26400	150 lbs	26400	26400
16	405	5	73	38100	150 lbs	38100	38100
16	405	5	73	42000	150 lbs	42000	42000
18	455	5	73	42000	150 lbs	42000	42000
20	508	5	73	73100	150 lbs	73100	73100
24	610	5	73	90000	150 lbs	90000	90000



Gasket

nominal width zoll/inch	inner-Ø mm	Outer-Ø mm	Sealing Thickness mm
2	51	100	8.0
3	76	134	8.0
4	102	163	8.0
5	127	185	8.0
6	152	213	8.0
8	204	264	8.0
10	254	315	8.0
12	305	365	8.0
14	355	418	8.0
16	405	467	8.0
18	455	511	8.0
20	508	567	8.0
24	610	667	8.0

